



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Bulb/Lamp & Electrical Connector Dielectric Grease

AAM Revised 11/02

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Bulb/Lamp & Electrical Connector Dielectric Grease is a silicone dielectric compound whose dielectric and lubricity properties facilitate and improve electrical connections. The compound prevents voltage leakage around any electrical connection. The compound is an excellent lubricant on rubber, plastic and ceramic surfaces and it also has good high temperature properties, thus preventing fusing of bulbs to sockets and other electrical connections.

PRODUCT BENEFITS

- Improves connections
- Prevents corrosion
- Eliminates voltage leakage
- High temperature properties
- Excellent rubber lubricant

TYPICAL APPLICATIONS

- Headlamps
- Lighting for instrument panel
- Glove compartment lights
- Interior courtesy lamps
- Parking lights and turn signals
- Brake lights
- Fuses
- Indicator lights
- Battery terminals

DIRECTIONS FOR USE

For Bulbs and Lamps

1. Make sure ignition system is off.
2. Coat the connector with the dielectric grease.
3. Screw bulb into socket and make sure of tight connection.

For connectors and battery terminals

1. Make sure the ignition system is off.
2. Clean surfaces with appropriate cleaner such as Permatex® Brake and Parts Cleaner or Battery Cleaner.
3. Coat both parts with grease.
4. Reassemble.

PROPERTIES OF UNCURED MATERIAL

	Typical Value
Chemical Type	Silicone dielectric compound
Appearance	Slightly translucent white
Specific Gravity	1.03
Viscosity	Grease
Flash Point, COC, °C (°F)	>260 (>500)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
31824	3 gram pouch

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-877)PERMATEX)