



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Date 12-Mar-2024

Version 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code 29208
Product Name THE RIGHT STUFF GASKET MAKER 5 FL.OZ
Unique Formula Identifier (UFI) Code ED5J-D0W5-U00H-QNKR
Other means of identification

Contains 2-BUTANONE OXIME

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sealant
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer ITW Permatex, Inc. 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex (866) 732-9502	Only Representative (OR) ITW Permatex, Inc. Bay 150 Shannon Industrial Estate Co. Clare Ireland V14 DF82 353(61)771500 353(61)471285 customerservice.shannon@itwpp.com
---	--

For further information, please contact

Contact Point ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

E-mail address: mail@permatex.com

Non-Emergency Telephone Number 866-732-9502

1.4. Emergency telephone number

24-hour emergency phone number - §45 - (EC)1272/2008	
Europe	112
Austria	01 406 43 43
Belgium	070 245 245
Denmark	+ 45 8212 1212
Finland	0800 147 111/ 09 471 977
France	+33 (0)1 45 42 59 59

Germany	+49 228 192 40
Ireland	01 809 2166
Italy	0382-24444
Netherlands	+31 (0)88 755 8000
Norway	22 59 13 00
Poland	112
Portugal	+351 800 250 250
Slovenia	112
Spain	+34 91 562 04 20
Sweden	112
Switzerland	145
United Kingdom	111
Bulgaria	+359 2 9154 233
Croatia	+3851 2348 342
Cyprus	1401
Czech Republic	+420 224 919 293/ +420 224 915 402
Estonia	16662/ (+372) 7943 794
Greece	(003) 2107793777
Hungary	+36 80 201 199
Iceland	543 2222
Latvia	+371 67042473
Liechtenstein	01 406 43 43
Lithuania	+370 (85) 2362052
Luxembourg	(+352) 8002 5500
Romania	+40213183606
Slovakia	+421 2 5477 4166
Malta	112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)

2.2. Label elements

Contains 2-BUTANONE OXIME



Signal word

Warning

Hazard statements

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H351 - Suspected of causing cancer

Precautionary Statements - EU (§28, 1272/2008)

P280 - Wear eye protection/ face protection.

P321 - Specific treatment (see .? on this label).

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

2.3. Other hazards

No information available.

Endocrine Disruptor Information**SECTION 3: Composition/information on ingredients****3.1 Substances**

Chemical name	Weight-%	REACH registration No.	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
CALCIUM CARBONATE 471-34-1	25 - <50%	Exempt	207-439-9	-	-	-	-
CARBON BLACK 1333-86-4	1 - <2.5%	Registration no. 01-211938482 2-32-XXXX	215-609-9 435-640-3	-	-	-	-
ALUMINIUM POWDER 7429-90-5	0.5 - <1%		(013-002-00-1) (013-001-00-6) 231-072-3	Flam. Sol. 1 (H228) Water-react. 2 (H261)	-	-	-
2-BUTANONE OXIME 96-29-7	0.1 - <0.5%		(616-014-00-0) 202-496-6	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) STOT SE 3 (H336) STOT SE 1 (H370) STOT RE 2 (H373)	-	-	-
MINERAL OIL 8042-47-5	0.1 - <0.5%		232-455-8	-	-	-	-

Full text of H- and EUH-phrases: see section 16**Acute Toxicity Estimate**

No information available

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
CALCIUM CARBONATE 471-34-1	6450	2000	3	No data available	No data available

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
CARBON BLACK 1333-86-4	15400	2000	0.0046	No data available	No data available
ALUMINIUM POWDER 7429-90-5	No data available	No data available	0.888	No data available	No data available
2-BUTANONE OXIME 96-29-7	100 + 930	1100 + 1000	No data available	No data available	No data available
MINERAL OIL 8042-47-5	5000	No data available	No data available	No data available	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove to fresh air.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Rinse mouth.
Self-protection of the first aider	See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
-----------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Effects of Exposure	No information available.
Note to physicians	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Small Fire	In case of fire, use water spray, foam, dry chemical, or CO ₂ .
Large Fire	In case of fire, use water spray, foam, dry chemical, or CO ₂ .
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the	No information available.
--	---------------------------

chemical

Hazardous combustion products No information available.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place.

Packaging materials No information available.

7.3. Specific end use(s)

Specific use(s)
Automotive Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
CALCIUM CARBONATE 471-34-1	-	-	-	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³
CARBON BLACK 1333-86-4	-	-	TWA: 3 mg/m ³	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
ALUMINIUM POWDER 7429-90-5	-	TWA: 10 mg/m ³ STEL 20 mg/m ³	TWA: 1 mg/m ³	TWA: 10.0 mg/m ³ TWA: 1.5 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³
2-BUTANONE OXIME 96-29-7	-	Sh+	-	-	-
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
CARBON BLACK 1333-86-4	-	TWA: 2.0 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
ALUMINIUM POWDER 7429-90-5	-	TWA: 10.0 mg/m ³	TWA: 5 mg/m ³ TWA: 2 mg/m ³ STEL: 10 mg/m ³ STEL: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 1.5 mg/m ³
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
CALCIUM CARBONATE 471-34-1	TWA: 10 mg/m ³	-	-	-	-
CARBON BLACK 1333-86-4	TWA: 3.5 mg/m ³	-	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³
ALUMINIUM POWDER 7429-90-5	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.25 mg/m ³ TWA: 10 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1 mg/m ³
2-BUTANONE OXIME 96-29-7	-	TWA: 0.3 ppm TWA: 1 mg/m ³ Sh+ H*	* skin sensitizer	-	-
MINERAL OIL 8042-47-5	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³ Peak: 20 mg/m ³	-	TWA: 5 mg/m ³
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
CALCIUM CARBONATE 471-34-1	-	-	-	TWA: 6 mg/m ³	-
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ STEL: 15 mg/m ³	-	TWA: 3 mg/m ³	-	-
ALUMINIUM POWDER 7429-90-5	TWA: 1 mg/m ³ STEL: 3 mg/m ³	-	TWA: 1 mg/m ³	TWA: 2 mg/m ³	TWA: 5 mg/m ³ TWA: 2 mg/m ³ TWA: 1 mg/m ³
2-BUTANONE OXIME 96-29-7	TWA: 3 ppm TWA: 10 mg/m ³ STEL: 10 ppm STEL: 33 mg/m ³ Sens+	-	-	-	-
MINERAL OIL 8042-47-5	-	-	-	TWA: 5 mg/m ³	-
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
CALCIUM CARBONATE 471-34-1	-	-	-	-	TWA: 10 mg/m ³
CARBON BLACK 1333-86-4	-	-	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 4 mg/m ³
ALUMINIUM POWDER 7429-90-5	-	-	-	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 2.5 mg/m ³ TWA: 1.2 mg/m ³
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³	-	TWA: 2 mg/m ³ TWA: 10 mg/m ³	-	TWA: 3.5 mg/m ³
ALUMINIUM POWDER 7429-90-5	TWA: 1 mg/m ³	TWA: 3 mg/m ³ TWA: 1 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³	-	TWA: 1 mg/m ³

		STEL: 10 mg/m ³ STEL: 3 mg/m ³			
2-BUTANONE OXIME 96-29-7	-	-	-	TWA: 1 mg/m ³ TWA: 0.3 ppm STEL: 2.4 ppm STEL: 8 mg/m ³ K*	-
MINERAL OIL 8042-47-5	-	-	-	TWA: 5 mg/m ³ STEL: 20 mg/m ³	-
Chemical name	Sweden		Switzerland		United Kingdom
CALCIUM CARBONATE 471-34-1	-		TWA: 3 mg/m ³ TWA: 10 mg/m ³		-
CARBON BLACK 1333-86-4	NGV: 3 mg/m ³		-		TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
ALUMINIUM POWDER 7429-90-5	NGV: 5 mg/m ³ NGV: 2 mg/m ³		TWA: 3 mg/m ³ TWA: 10 mg/m ³		TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
MINERAL OIL 8042-47-5	-		TWA: 5 mg/m ³		-

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Bulgaria	Croatia	Czech Republic
CARBON BLACK 1333-86-4	-	(-)	-	-	-
ALUMINIUM POWDER 7429-90-5	-	60 µg/g Creatinine (urine - Aluminum after end of work day, at the end of a work week/end of the shift) (-)	-	200 µg/L - urine (Aluminum) - at the end of the work shift	-
Chemical name	Denmark	Finland	France	Germany DFG	Germany TRGS
ALUMINIUM POWDER 7429-90-5	-	-	-	50 µg/g Creatinine (urine - Aluminum for long-term exposures: at the end of the shift after several shifts) 50 µg/g Creatinine - BAT (for long-term exposures: at the end of the shift after several shifts) urine 15 µg/g Creatinine - BAR (for long-term exposures: at the end of the shift after several shifts) urine	50 µg/g Creatinine (urine - Aluminum for long-term exposures: at the end of the shift after several shifts)
Chemical name	Latvia	Luxembourg	Romania	Slovakia	
ALUMINIUM POWDER 7429-90-5	-	-	200 µg/L - urine (Aluminum) - end of shift	60 µg/g creatinine (urine - Aluminum not critical)	
Chemical name	Slovenia	Spain	Switzerland	United Kingdom	
ALUMINIUM POWDER 7429-90-5	50 µg/L - urine (Aluminum) - for long-term exposure: at the end of the work shift after several consecutive	-	50 µg/g creatinine (urine - Aluminum after several shifts (for long-term exposures)) 0.21 µmol/mmol	-	

	workdays		creatinine (urine - Aluminum after several shifts (for long-term exposures))	
--	----------	--	--	--

8.2. Exposure controls**Derived No Effect Level (DNEL) - Workers** No information available

Chemical name	Oral	Dermal	Inhalation
2-BUTANONE OXIME 96-29-7	-	1.3 mg/kg bw/day [4] [6] 2.5 mg/kg bw/day [4] [7]	9 mg/m ³ [4] [6] 3.33 mg/m ³ [5] [6]

Derived No Effect Level (DNEL) - General Public No information available.

Chemical name	Oral	Dermal	Inhalation
2-BUTANONE OXIME 96-29-7	-	1.5 mg/kg bw/day [4] [6] 1.5 mg/kg bw/day [4] [7]	2.7 mg/m ³ [4] [6] 2 mg/m ³ [5] [6]

Predicted No Effect Concentration (PNEC) No information available.

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
2-BUTANONE OXIME 96-29-7	0.256 mg/L	0.118 mg/L	-	-	-

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
2-BUTANONE OXIME 96-29-7	-	-	177 mg/L	-	-

Personal protective equipment**Eye/face protection** No special protective equipment required.**Skin and body protection** No special protective equipment required.**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.**Thermal hazards** No information available.**Other protective equipment** No information available.**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.**Environmental exposure controls** No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Paste / Gel Liquid
Appearance	Black
Color	Black
Odor	Mild
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	Polymerization
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	> 95 °C	Tag Closed Cup
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	
pH (as aqueous solution)	No data available	No information available
Kinematic viscosity	No Data Available	None known
Dynamic viscosity	No data available	None known
Water solubility	No data available	Not applicable
Solubility(ies)	No Data Available	Polymerization
Partition coefficient	No Data Available	None known
Vapor pressure	<5 mmHg @ 70°F	
Relative density	1.34	
Bulk density	No data available	
Density	No data available	
Vapor density	3	Air = 1
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
None known		

9.2. Other information

VOC content	<3%
Formula	No information available

9.2.1. Information with regard to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
 Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization No information available.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous Decomposition Products Carbon oxides. Nitrogen oxides (NOx). Formaldehyde. May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Information on likely routes of exposure****Product Information**

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity**Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 12,486.10 mg/kg

ATEmix (dermal) 31,958.00 mg/kg

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
CARBON BLACK	> 15400 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 4.6 mg/m ³ (Rat) 4 h
ALUMINIUM POWDER	-	-	> 0.888 mg/L (Rat) 4 h
2-BUTANONE OXIME	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
MINERAL OIL	> 5000 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Chemical name	European Union
2-BUTANONE OXIME	Carc. 1B

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

11.2. Information on other hazards**11.2.1. Endocrine disrupting properties**

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information**12.1. Toxicity**

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-BUTANONE OXIME	EC50: =83mg/L (72h, <i>Desmodesmus subspicatus</i>)	LC50: 777 - 914mg/L (96h, <i>Pimephales promelas</i>) LC50: =760mg/L (96h, <i>Poecilia reticulata</i>)	-	EC50: =750mg/L (48h, <i>Daphnia magna</i>)
MINERAL OIL	-	LC50: >10000mg/L (96h, <i>Lepomis macrochirus</i>)	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient
2-BUTANONE OXIME	0.65
MINERAL OIL	6

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
CALCIUM CARBONATE	The substance is not PBT / vPvB
CARBON BLACK	The substance is not PBT / vPvB
ALUMINIUM POWDER	The substance is not PBT / vPvB
2-BUTANONE OXIME	The substance is not PBT / vPvB
MINERAL OIL	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Other Information No information available.

SECTION 14: Transport information

IATA

- 14.1 UN number or ID number Not regulated
 14.2
 14.3 Transport hazard class(es) Not regulated
 14.4 Packing group Not regulated
 14.5 Environmental hazard Not applicable
 14.6 Special precautions for user

IMDG

- 14.1 UN number or ID number Not regulated
 14.2
 14.3 Transport hazard class(es) Not regulated
 14.4 Packing Group Not regulated
 14.5 Environmental hazard Not applicable

14.6 Special precautions for user**14.7 Maritime transport in bulk according to IMO instruments****RID**

14.1 UN/ID No	Not regulated
14.2	
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	

ADR

14.1 UN number or ID number	Not regulated
14.2	
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Chemical name	French RG number
CARBON BLACK - 1333-86-4	RG 16, RG 16bis
ALUMINIUM POWDER - 7429-90-5	RG 32 RG 16, RG 16bis
MINERAL OIL - 8042-47-5	RG 36bis

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
2-BUTANONE OXIME	Present	-	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
CALCIUM CARBONATE - 471-34-1	75.	-
CARBON BLACK - 1333-86-4	75.	-
ALUMINIUM POWDER - 7429-90-5	75.	-
2-BUTANONE OXIME - 96-29-7	75. 28.	-

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Chemical name	EU - Plant Protection Products (1107/2009/EC)
CALCIUM CARBONATE - 471-34-1	Plant protection agent
CARBON BLACK - 1333-86-4	Plant protection agent
MINERAL OIL - 8042-47-5	Plant protection agent

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**15.2. Chemical safety assessment****Chemical Safety Report** No information available**SECTION 16: Other information****Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

H228 - Flammable solid
H261 - In contact with water releases flammable gas
H312 - Harmful in contact with skin
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H351 - Suspected of causing cancer

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision Date 12-Mar-2024

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet

EU SDS version information - EGHS

UL release:
 GHS Revision 7
 2023 Q1

Full text of H-Statements referred to under section 3 H228 - Flammable solid H261 - In contact with water releases flammable gas H312 - Harmful in contact with skin H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H351 - Suspected of causing cancer

Chemical name	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)
ALUMINIUM POWDER	Flam. Sol. 1 (H228) Water-react. 2 (H261)	
2-BUTANONE OXIME	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) STOT SE 3 (H336) STOT SE 1 (H370) STOT RE 2 (H373)	

Chemical name	CAS No.	French RG number
CARBON BLACK	1333-86-4	RG 16, RG 16bis
ALUMINIUM POWDER	7429-90-5	RG 32 RG 16, RG 16bis
MINERAL OIL	8042-47-5	RG 36bis

VOC content