



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Date 25-Jun-2024

Version 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code 85120
Product Name LIQUID ELECTRICAL TAPE 4 OZ
Unique Formula Identifier (UFI) Code 4TYH-H01C-X00C-QFQJ
Other means of identification

Contains XYLENE, ACETONE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sealant
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer ITW Permatex, Inc. 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex (866) 732-9502	Only Representative (OR) ITW Permatex, Inc. Bay 150 Shannon Industrial Estate Co. Clare Ireland V14 DF82 353(61)771500 353(61)471285 customerservice.shannon@itwpp.com
---	--

For further information, please contact

Contact Point ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

E-mail address: mail@permatex.com

1.4. Emergency telephone number

24-hour emergency phone number - §45 - (EC)1272/2008	
Europe	112
Austria	01 406 43 43
Belgium	070 245 245
Denmark	+ 45 8212 1212
Finland	0800 147 111/ 09 471 977
France	+33 (0)1 45 42 59 59
Germany	+49 228 192 40

Ireland	01 809 2166
Italy	0382-24444
Netherlands	+31 (0)88 755 8000
Norway	22 59 13 00
Poland	112
Portugal	+351 800 250 250
Slovenia	112
Spain	+34 91 562 04 20
Sweden	112
Switzerland	145
United Kingdom	111
Bulgaria	+359 2 9154 233
Croatia	+3851 2348 342
Cyprus	1401
Czech Republic	+420 224 919 293/ +420 224 915 402
Estonia	16662/ (+372) 7943 794
Greece	(003) 2107793777
Hungary	+36 80 201 199
Iceland	543 2222
Latvia	+371 67042473
Liechtenstein	01 406 43 43
Lithuania	+370 (85) 2362052
Luxembourg	(+352) 8002 5500
Romania	+40213183606
Slovakia	+421 2 5477 4166
Malta	112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flammable liquids	Category 2 - (H225)
Acute toxicity - Dermal	Category 4 - (H312)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H335,H336)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains XYLENE, ACETONE



Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor. H312 - Harmful in contact with skin. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H332 - Harmful if inhaled. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H412 - Harmful to aquatic life with long lasting effects.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P312 - Call a POISON CENTER or doctor if you feel unwell. P370 + P378 - In case of fire: Use dry chemical, CO₂, water spray or

alcohol-resistant foam to extinguish. P501 - Dispose of contents/ container to an approved waste disposal plant.

- 31 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
- 31 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
- 98 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
- 80 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
- 55.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Harmful to aquatic life.

Endocrine Disruptor Information

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Weight-%	REACH registration No.	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
XYLENE 1330-20-7	25 - <50%		(601-022-00-9) 215-535-7	Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Flam. Liq. 3 (H226)	-	-	-
METHYL ETHYL KETONE (BUTANONE) 78-93-3	10 - <20%		(606-002-00-3) 201-159-0	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-
ACETONE 67-64-1	1-10	Registration no: 01-211947133 0-49-XXXX	(606-001-00-8) 200-662-2	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

No information available

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
XYLENE 1330-20-7	3500	4350	No data available	No data available	No data available

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
METHYL ETHYL KETONE (BUTANONE) 78-93-3	2483	5000	No data available	34.5018	No data available
ACETONE 67-64-1	5800	15700	100.2	No data available	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove to fresh air.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
-----------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Effects of Exposure	No information available.
Note to physicians	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	No information available.
---	---------------------------

5.3. Advice for firefighters

Special protective equipment and	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.
---	---

precautions for fire-fighters Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place.

7.3. Specific end use(s)

Specific use(s)
Automotive Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
XYLENE 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³	STEL: 100 ppm STEL: 442 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³

	STEL: 100 ppm STEL: 442 mg/m ³ *	STEL 100 ppm STEL 442 mg/m ³	STEL: 100 ppm STEL: 442 mg/m ³ D*	TWA: 50 ppm TWA: 221.0 mg/m ³ K*	STEL: 100 ppm STEL: 442 mg/m ³ *
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 100 ppm TWA: 295 mg/m ³ STEL 200 ppm STEL 590 mg/m ³ H*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	STEL: 885 mg/m ³ TWA: 590 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³
ACETONE 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL 2000 ppm STEL 4800 mg/m ³	TWA: 246 ppm TWA: 594 mg/m ³ STEL: 492 ppm STEL: 1187 mg/m ³	STEL: 1400 mg/m ³ TWA: 600 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
XYLENE 1330-20-7	* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 200 mg/m ³ Ceiling: 400 mg/m ³ D*	TWA: 25 ppm TWA: 109 mg/m ³ H* STEL: 442 mg/m ³ STEL: 100 ppm	TWA: 50 ppm TWA: 200 mg/m ³ TWA: 5 mg/m ³ TWA: 100 mg/m ³ TWA: 20 ppm STEL: 100 ppm STEL: 450 mg/m ³ STEL: 500 mg/m ³ A*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 440 mg/m ³ iho*
METHYL ETHYL KETONE (BUTANONE) 78-93-3	STEL: 300 ppm STEL: 900 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³	TWA: 600 mg/m ³ Ceiling: 900 mg/m ³	TWA: 50 ppm TWA: 145 mg/m ³ H* STEL: 900 mg/m ³ STEL: 300 ppm	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 20 ppm TWA: 60 mg/m ³ STEL: 100 ppm STEL: 300 mg/m ³ iho*
ACETONE 67-64-1	* TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 800 mg/m ³ Ceiling: 1500 mg/m ³	TWA: 250 ppm TWA: 600 mg/m ³ STEL: 500 ppm STEL: 1200 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 630 ppm STEL: 1500 mg/m ³
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
XYLENE 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ TWA: 1000 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ STEL: 1500 mg/m ³ *	TWA: 50 ppm TWA: 220 mg/m ³ H*	TWA: 50 ppm TWA: 220 mg/m ³ Peak: 100 ppm Peak: 440 mg/m ³ *	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 650 mg/m ³ *	TWA: 221 mg/m ³ TWA: 50 ppm STEL: 442 mg/m ³ STEL: 100 ppm b*
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ *	TWA: 200 ppm TWA: 600 mg/m ³ H*	TWA: 200 ppm TWA: 600 mg/m ³ Peak: 200 ppm Peak: 600 mg/m ³ *	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 600 mg/m ³ TWA: 200 ppm STEL: 900 mg/m ³ STEL: 300 ppm b*
ACETONE 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1000 ppm STEL: 2420 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ Peak: 1000 ppm Peak: 2400 mg/m ³	TWA: 1780 mg/m ³ STEL: 3560 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
XYLENE 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Sk*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ cute*	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Ada*	O* TWA: 221 mg/m ³ TWA: 50 ppm STEL: 442 mg/m ³ STEL: 100 ppm
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Sk*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	TWA: 67 ppm TWA: 200 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	-
ACETONE 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 250 ppm TWA: 594 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³

	STEL: 1500 ppm STEL: 3630 mg/m ³		STEL: 500 ppm STEL: 1187 mg/m ³		STEL: 1000 ppm STEL: 2420 mg/m ³
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
XYLENE 1330-20-7	Peau* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	skin* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 47.5 ppm TWA: 210 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ H*	TWA: 25 ppm TWA: 108 mg/m ³ STEL: 37.5 ppm STEL: 135 mg/m ³ H*	STEL: 200 mg/m ³ TWA: 100 mg/m ³ skóra*
METHYL ETHYL KETONE (BUTANONE) 78-93-3	STEL: 300 ppm STEL: 900 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³	STEL: 300 ppm STEL: 900 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³	TWA: 197 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ H*	TWA: 75 ppm TWA: 220 mg/m ³ STEL: 112.5 ppm STEL: 275 mg/m ³	STEL: 900 mg/m ³ TWA: 450 mg/m ³ skóra*
ACETONE 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1 ppm STEL: 2420 mg/m ³	TWA: 125 ppm TWA: 295 mg/m ³ STEL: 156.25 ppm STEL: 368.75 mg/m ³	STEL: 1800 mg/m ³ TWA: 600 mg/m ³
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
XYLENE 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Cutânea*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ P*	TWA: 50 ppm TWA: 221 mg/m ³ K* Ceiling: 442 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ K*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ vía dérmica*
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ Ceiling: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ K*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³
ACETONE 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 750 ppm	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 2420 mg/m ³ STEL: 1000 ppm	TWA: 500 ppm TWA: 1210 mg/m ³
Chemical name	Sweden		Switzerland		United Kingdom
XYLENE 1330-20-7	NGV: 50 ppm NGV: 221 mg/m ³ Bindande KGV: 100 ppm Bindande KGV: 442 mg/m ³ H*		TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 440 mg/m ³ H*		TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 441 mg/m ³ Sk*
METHYL ETHYL KETONE (BUTANONE) 78-93-3	NGV: 50 ppm NGV: 150 mg/m ³ Bindande KGV: 300 ppm Bindande KGV: 900 mg/m ³		TWA: 200 ppm TWA: 590 mg/m ³ STEL: 200 ppm STEL: 590 mg/m ³ H*		TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*
ACETONE 67-64-1	NGV: 250 ppm NGV: 600 mg/m ³ Vägledande KGV: 500 ppm Vägledande KGV: 1200 mg/m ³		TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³		TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Bulgaria	Croatia	Czech Republic
XYLENE 1330-20-7	-	1.5 g/L (urine - Methylhippuric acid after end of work day, at the end of a work week/end of the shift)	-	1.50 mg/L - blood (Xylene) - at the end of the work shift 1.50 g/g Creatinine - urine (Methylhippuric acid) - at the end of the work shift	820 µmol/mmol Creatinine (urine - Methylhippuric acid end of shift) 1400 mg/g Creatinine (urine - Methylhippuric acid end of shift)

METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	-	-	2.6 mg/g Creatinine - urine (Ethyl methyl ketone) - at the end of the work shift	-
ACETONE 67-64-1	-	-	80 mg/L - urine (Acetone) - at the end of exposure or end of work shift	20.0 mg/L - blood (Acetone) - at the end of the work shift 20.0 mg/g Creatinine - urine (Acetone) - at the end of the work shift	-
Chemical name	Denmark	Finland	France	Germany DFG	Germany TRGS
XYLENE 1330-20-7	-	5.0 mmol/L (urine - Methylhippuric acid after the shift)	- urine (Methylhippuric acid) - end of shift	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of shift) 2000 mg/L - BAT (end of exposure or end of shift) urine	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of shift)
METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	-	- urine (Methylethylketone) - end of shift	2 mg/L (urine - 2-Butanone end of shift) 2 mg/L - BAT (end of exposure or end of shift) urine	2 mg/L (urine - 2-Butanone end of shift)
ACETONE 67-64-1	-	-	- urine (Acetone) - end of shift	50 mg/L (urine - Acetone end of shift) 50 mg/L - BAT (end of exposure or end of shift) urine 2.5 mg/L - BAR (end of exposure or end of shift) urine	50 mg/L (urine - Acetone end of shift)
Chemical name	Hungary	Ireland	Italy MDLPS	Italy AIDII	
XYLENE 1330-20-7	1500 mg/g Creatinine (urine - Methyl hippuric acid end of shift) 860 µmol/mmol Creatinine (urine - Methyl hippuric acid end of shift)	1.5 g/g Creatinine (urine - Methylhippuric acids end of shift)	-	1.5 g/g Creatinine - urine (Methylhippuric acid) - end of shift	
METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	70 µmol/L (urine - Butan-2-one post shift)	-	2 mg/L - urine (MEK) - end of shift	
ACETONE 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-	25 mg/L - urine (Acetone) - end of shift	
Chemical name	Latvia	Luxembourg	Romania	Slovakia	
XYLENE 1330-20-7	-	-	3 g/L - urine (Methylhippuric acid) - end of shift	1.5 mg/L (blood - Xylene end of exposure or work shift) 2000 mg/L (urine - Methylhippuric acid end of exposure or work shift)	
METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	-	2 mg/L - urine (Methylethylketone) - end of shift	-	
ACETONE 67-64-1	-	-	50 mg/L - urine (Acetone) - end of shift	80 mg/L (urine - Acetone end of exposure or work shift)	
Chemical name	Slovenia	Spain	Switzerland	United Kingdom	
XYLENE 1330-20-7	2 g/L - urine (Methylhippuric acid (all	1 g/g Creatinine (urine - Methylhippuric acids end	2 g/L (urine - Methylhippuric acid end of	650 mmol/mol creatinine - urine (Methyl hippuric	

	isomers)) - at the end of the work shift	of shift)	shift)	acid) - post shift
METHYL ETHYL KETONE (BUTANONE) 78-93-3	2 mg/L - urine (2-Butanone) - at the end of the work shift	2 mg/L (urine - Methyl ethyl ketone end of shift)	2 mg/L (urine - 2-Butanone end of shift, before subsequent shift or 16 hour) 27.7 µmol/L (urine - 2-Butanone end of shift, before subsequent shift or 16 hour)	70 µmol/L - urine (Butan-2-one) - post shift
ACETONE 67-64-1	80.0 mg/L - urine (Acetone) - at the end of the work shift	50 mg/L (urine - Acetone end of shift)	50 mg/L (urine - Acetone end of shift) 0.86 mmol/L (urine - Acetone end of shift)	-

8.2. Exposure controls

Derived No Effect Level (DNEL) - Workers No information available

Derived No Effect Level (DNEL) - General Public No information available.

Predicted No Effect Concentration (PNEC) No information available.

Personal protective equipment

Eye/face protection No special protective equipment required.

Skin and body protection No special protective equipment required.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Black
Color	No information available
Odor	Solvent
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	80 °C	
Boiling point / boiling range	82 °C	
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	7 °C	CC (closed cup)
Autoignition temperature	No data available	None known

Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	No information available
Kinematic viscosity	2000 cP	
Dynamic viscosity	No data available	None known
Water solubility	No data available	
Solubility(ies)	No Data Available	None known
Partition coefficient	No Data Available	None known
Vapor pressure	12.6 kPa	
Relative density	0.96	
Bulk density	No data available	
Density	No data available	
Vapor density	2.4	Air = 1
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

VOC content 60.5

9.2.1. Information with regard to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available < 1 Ether = 1

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous Decomposition Products Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Information on likely routes of exposure**

Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity**Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	3,368.10 mg/kg
ATEmix (dermal)	1,672.50 mg/kg
ATEmix (inhalation-dust/mist)	1.7765 mg/l
ATEmix (inhalation-vapor)	13,000.00 mg/l

31 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
 31 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
 98 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
 80 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
 55.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
XYLENE	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
METHYL ETHYL KETONE (BUTANONE)	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
ACETONE	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity The environmental impact of this product has not been fully investigated.

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
XYLENE	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)
METHYL ETHYL KETONE (BUTANONE)	-	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	-	EC50: >520mg/L (48h, Daphnia magna) EC50: =5091mg/L (48h, Daphnia magna) EC50: 4025 - 6440mg/L (48h, Daphnia magna)
ACETONE	-	LC50: 4.74 - 6.33mL/L	-	EC50: 10294 -

		(96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)		17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
--	--	---	--	--

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient
XYLENE	3.15
METHYL ETHYL KETONE (BUTANONE)	0.3
ACETONE	-0.24

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
XYLENE	The substance is not PBT / vPvB
METHYL ETHYL KETONE (BUTANONE)	The substance is not PBT / vPvB
ACETONE	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number ID 8000
14.2 Proper shipping name Consumer commodity
14.3 Transport hazard class(es) 9
14.4 Packing group Not regulated

14.5 Environmental hazard Not applicable

14.6 Special precautions for user

IMDG

14.1 UN number or ID number UN1133
 14.2 Proper shipping name Adhesives Limited Quantity (LQ)
 14.3 Transport hazard class(es) 3
 14.4 Packing Group II
 14.5 Environmental hazard Not applicable
 14.6 Special precautions for user
 14.7 Maritime transport in bulk according to IMO instruments

RID

14.1 UN/ID No UN1133
 14.2 Proper shipping name Adhesives Limited Quantity (LQ)
 14.3 Transport hazard class(es) 3
 14.4 Packing Group II
 14.5 Environmental hazard Not applicable
 14.6 Special precautions for user

ADR

14.1 UN number or ID number UN1133
 14.2 Proper shipping name Adhesives Limited Quantity (LQ)
 14.3 Transport hazard class(es) 3
 14.4 Packing Group II
 14.5 Environmental hazard Not applicable
 14.6 Special precautions for user
 Classification code F1

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical name	French RG number
XYLENE - 1330-20-7	RG 4bis, RG 84
METHYL ETHYL KETONE (BUTANONE) - 78-93-3	RG 84
ACETONE - 67-64-1	RG 84

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
XYLENE	-	-	Development Category 2

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
XYLENE - 1330-20-7	75.	-
METHYL ETHYL KETONE (BUTANONE) - 78-93-3	75.	-
ACETONE - 67-64-1	75.	-

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

15.2. Chemical safety assessment**Chemical Safety Report** No information available**SECTION 16: Other information****Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

EUH066 - Repeated exposure may cause skin dryness or cracking
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness

Legend

SVHC: Substances of Very High Concern for Authorization:
vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapor	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method

Serious eye damage/eye irritation	Calculation method
Respiratory sensitization	Calculation method
Skin sensitization	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGl(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 Japan GHS Classification
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision Date 25-Jun-2024

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet

EU SDS version information - EGHS

UL release:
 GHS Revision 7
 2023 Q1

Specific target organ toxicity (single exposure)	Category 3
--	------------

Full text of H-Statements referred to under section 3 EUH066 - Repeated exposure may cause skin dryness or cracking H225 - Highly flammable liquid and vapor H226 - Flammable liquid and vapor H312 - Harmful in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H336 - May cause drowsiness or dizziness

Chemical name	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)
XYLENE	Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Flam. Liq. 3 (H226)	
METHYL ETHYL KETONE (BUTANONE)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	
ACETONE	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	

Chemical name	CAS No.	French RG number
XYLENE	1330-20-7	RG 4bis, RG 84
METHYL ETHYL KETONE (BUTANONE)	78-93-3	RG 84
ACETONE	67-64-1	RG 84

VOC content